

Covert Mirror Camera

KC-3172



- ATM use
- 420 TVL
- 1/3"SONY CCD+SONY 11R DSP.
- Cable Management Bracket



| Specifications | |
|------------------------|---|
| Sensor Chip | 1/3" SONY CCD / SONY 11R DSP |
| Effective Pixels | NTSC: 510 (H) × 492 (V) PAL: 500 (H) × 582 (V) |
| Scanning Frequency | NTSC:15734Hz(H) 60Hz(V) PAL:15625Hz(H) 50Hz(V) |
| High Resolution | 420 TVL |
| Sensitivity | 0.1 Lux |
| Synchronizing System | Internal Sync., 2:1 Interlace |
| Auto White Balance | AUTO |
| Auto Gain Control | AUTO |
| Backlight Compensation | AUTO |
| S/N Ratio | More than 48dB (AGC OFF) |
| Gamma Compensation | 0.45 |
| Electronic Shutter | Auto 【 1/60(50)~1/100,000 】 |
| Video Output | 1.0Vp-p75Ω |
| Lens Mount | 3.6 mm Standard Board Lens |
| Power Requirement | DC 12V / 105mA |
| Dimension / Weight | 95 (∅) x 110(D) mm ; 500g |
| Operating Temperature | -10℃ ~ +50℃ |