

SPEED DOME CAMERA

ENOS 1/3" ZTR-PT4-32X



FEATURES:

- 360 Degree Continues Rotation
- Pan range: 0 °~ 360 °Continue
- Tilt range: 0 °~90 °Flip
- Pan Speed: Max 60 °/ Sec
- Preset point: 32
- RS485 control
- Lens: Optional



SPECIFICATIONS

Internal camera	1/3" Sony 420TVL
Lens	5-15 mm varifocal lens (4-9mm Lens is optional)
Power Supply	DC12V 500mA
Communication	RS485 (+/-)
Protocol	Pelco-P/D
Baudrate	1200/2400/4800/9600 bps
Pan range	0°~360° Continue
Tilt range	0°~90° Flip
Pan Speed	Max 60°/ Sec
Preset Point	32
Auto Scan	Yes (Programmable speed and left right limited point)
Home Position	Yes (Programmable auto come back home position)
Protection	IP66 for outdoor use
Size	∅ 125x210mm
Weight	2.2KGS

Design & Specification are subject to change without notice

YOUR'S SMART SECURITY PROVIDER



GENX TECHNOLOGY (M) SDN BHD

NO.68-2, JALAN DWITASIK, DATARAN DWITASIK, BANDAR SRI PERMAISURI, 56000 KUALA LUMPUR, MALAYSIA

TEL: 03-9171 1988 FAX:03-9171 4988

